



## Technical & Environmental Specification

Main Power Supply	~230 ± 10%
Frequency	50/60Hz
Back-up Power Supply	1 battery, 12V/7Ah
Power availability	0.7A
Main Power supply fail consumption	125mA
Outputs (Sounder circuits on the control PCB module)	2; 24V / 0.5A Fuse
Output, FAULT Relay	1;3A@24VDC
Output, Fire Relay	1;3A@24VDC
Auxiliary output	24VDC/0.3A fuse
Fixed Zones	8
Detectors per zone/max. number of detectors	32/256
Multi language front panels	YES
Operating temperature	0°C to +40°C
Relative humidity resistance	(93 ± 3)% @40°C
Weight (w/o battery)	~2.4kg

## Features

- 8 Fixed Zones
- Supports up to 256 detectors
- Unlimited call points
- 1 “fire” and 1 “fault” relay outputs
- 2 monitored sounder outputs
- Active EOL allowing continuous monitoring of inputs
- Walk test
- LED indication
- Levels of access protected by means of security key
- Plastic box


## Description

The Eagle 8 conventional fire alarm panel provides 8 fixed zones. With up to 32 fire detectors and unlimited call points that can be connected to every fire zones. The Eagle 8 is situated in a plastic box. The panel is easy for installation and maintenance and provides user-friendly daily operations. The panel is suitable for residential, small and middle office applications with protected area up to 3000m2. The panel is available in different language versions for the front panel.

## Packing Details

Single packing box	1 unit of Eagle 8 Fire alarm panel, dimensions 342x295x103mm
Carton packing box	5 units of Eagle 8 Fire alarm panel, dimensions 560x362x320mm

## Dimension Details



## Connection Diagram

